GTI-500 参数

最大交流输入功率	500WP
额定功率	500W
DC 最大电压	30VDC
DC 电压范围	10.5V~28VDC
AC 标准电压范围	90~140VAC
AC 频率范围	55-63Hz
尺寸	21*16.5*5.3 cm



最大输出功率因数	99%
输出电流总谐波失真	THDIAC<5%
相位差	<1%
岛效应保护	VAC;fAC
输出短路保护	限流
显示	LED
安装	壁挂
冷却	风扇
待机功耗	<2W
夜间功耗	<1W
反压保护	Fuse
认证	CE
环境温度	0~99%(Indoor Type Design)
防水	Indoor Type Design
电磁兼容	EN50081.part1 EN50082.part1
电网扰动	EN61000-3-2 En60950-1
电网检测	DIN VDE 126

GTI-500 Parameter

DC Maximum Input Power	500WP	
Rated Power	500W	
DC Maximum Voltage	30VDC	
DC Voltage Range	10.5V~28VDC	
AC standard voltage range	90~140VAC	
AC Frequency Range	55-63Hz	
Size	21*16.5*5.3 cm	
Maximum Output Power Factor	99%	
Output Current Total Harmonic Distortion	THDIAC<5%	
Phase	<1%	
Islanding Protection	VAC;fAC	
Output Short Circuit Protection	Current-limiting	
Show	LED	
Installation	Wall hanging	
Cooling	Fan	
Standby Power	<2W	
Night Power	<1W	
Anti-Voltage Protection	Fuse	
Certificate	CE	
Humidity	0~99%(Indoor Type Design)	
Waterproof	Indoor Type Design	
Electromagnetic Compatibility	EN50081.part1 EN50082.part1	
Power System Disturbance	EN61000-3-2 En60950-1	
Network Test	DIN VDE 126	